

Laeventilaatorid



Decorative HTD and HTL



HTS STANDARD



HTB 150N IP55



HTB N STANDARD

Tüüp	Võimsus (kW)	Pinge (V)	Vool (A)	Pöörete arv (x/min)	Õhukogus (m³/h)	Surve max Pa	Kaal (kg)	Mürategur (dB)	Töötemperatuur (C)	IP kaitseaste
HTD-130 B	0.055	230	---	200	6000	---	5.5	46	0	IP44
HTD-130 MR	0.055	230	---	200	6000	---	5.5	46	0	IP44
HTL-130 1G	0.055	230	---	200	6000	---	7.5	46	0	IP44
HTL-130 4F	0.06	230	---	200	6000	---	7	46	0	IP44
HTS-140	0.05	230	---	226	6000	---	5.5	46	0	IP44
HTS-90	0.045	230	---	380	4000	---	5.2	45	0	IP44
HTB - 150 N IP 55	0.072	230	---	240	13000	---	9.2	47	0	IP55
HTB - 150 N	0.075	230	---	220	12600	---	8.2	47	0	IP44
HTB - 75 N	0.045	230	---	280	6400	---	4.8	45	0	IP44
HTB - 90 N	0.06	230	---	240	8650	---	5.2	46	0	IP44