

Axiaal kanaliventilaatorid


KAN Plahvatuskaitsega KANReeversiga



KV Seeria



KAN Turbo



AFK



KAN Seeria



AFS



AFH



AFD



AFC-VB



AFC



Tüüp	Võimsus (kW)	Pinge (V)	Vool (A)	Pöörete arv (x/min)	Õhukogus (m ³ /h)	Surve max Pa	Kaal (kg)	Mürategur (dB)	Töötempe ratuur (C)	IP kaitseaste
315/ KAN/ 10- 10/4 5/40 0/H/ Ex	0.75	400V	1.8	2760	5170	690	20	82	-20 +40	IP 56
355/ KAN/ 10- 10/3 0/40 0/H/ Ex	0.75	400V	1.8	2760	4460	900	23	76	-20 +40	IP 56
355/ KAN/ 10- 10/4 5/40 0/N/ Ex	0.18	400V	0.6	1370	3520	210	28	71	-20 +40	IP 56
400/ KAN/ 10- 10/3 0/40 0/H/ Ex	1.1	400V	2.4	2760	7010	900	25	82	-20 +40	IP 56
400/ KAN/ 10- 10/4	0.37	400V	1.3	1420	5440	255	24	76	-20 +40	IP 56

<u>5/40</u> <u>0/N/</u> <u>Ex</u>										
<u>400/</u> <u>KAN/</u> <u>8-</u> <u>8/35</u> <u>/400</u> <u>/H/E</u> <u>x</u>	1.5	400V	3.5	2850	8680	930	29	86	-20 +40	IP 56
<u>450/</u> <u>KAN/</u> <u>10-</u> <u>10/4</u> <u>5/40</u> <u>0/N/</u> <u>Ex</u>	0.55	400V	1.7	1420	7860	300	26	69	-20 +40	IP 56
<u>500/</u> <u>KAN/</u> <u>10-</u> <u>10/4</u> <u>5/40</u> <u>0/N/</u> <u>Ex</u>	0.75	400V	2.1	1370	9910	310	30	81	-20 +40	IP 56
<u>500/</u> <u>KAN/</u> <u>8-</u> <u>8/40</u> <u>/400</u> <u>/N/E</u> <u>x</u>	0.55	400V	1.7	1420	8740	290	31	79	-20 +40	IP 56
<u>500/</u> <u>KAN/</u> <u>8-</u> <u>8/50</u> <u>/400</u> <u>/N/E</u> <u>x</u>	0.75	400V	2.1	1370	10300	270	30	82	-20 +40	IP 56
<u>560/</u> <u>KAN/</u> <u>10-</u> <u>10/4</u> <u>0/40</u> <u>0/N/</u> <u>Ex</u>	0.75	400V	2.1	1370	11700	340	35	81	-20 +40	IP 56
<u>560/</u> <u>KAN/</u> <u>3-</u> <u>6/30</u> <u>/400</u> <u>/H/E</u> <u>x</u>	1.1	400V	2.4	2780	12900	540	36	83	-20 +40	IP 56
<u>560/</u> <u>KAN/</u> <u>4-</u> <u>8/25</u>	1.1	400V	2.4	2780	12200	670	36	82	-20 +40	IP 56

<u>/400 /H/E x</u>										
<u>400/ KAN/ 12- 12/4 5/40 0/RE W</u>	0.37	400	1.2	1400	4290	165	25	74	-20 +60	IP 66
<u>450/ KAN/ 10- 10/4 5/40 0/RE W</u>	0.37	400	1.2	1400	6510	180	25	79	-20 +60	IP 66
<u>500/ KAN/ 12- 12/4 0/40 0/RE W</u>	0.55	400	1.3	1400	7430	180	29	78	-20 +60	IP 66
<u>500/ KAN/ 6- 6/45 /400 /RE W</u>	0.37	400	1.2	1400	7740	155	27	79	-20 +60	IP 66
<u>500/ KAN/ 8- 8/40 /400 /RE W</u>	0.37	400	1.2	1400	7240	180	27	78	-20 +60	IP 66
<u>560/ KAN/ 12- 12/4 0/40 0/RE W</u>	0.75	400	2.2	1400	10200	275	33	81	-20 +60	IP 66
<u>560/ KAN/ 6- 6/40 /400 /RE W</u>	0.37	400	1.2	1400	8560	160	28	77	-20 +60	IP 66
<u>560/ KAN/ 8- 8/40</u>	0.55	400	1.3	1400	9380	190	29	79	-20 +60	IP 66

<u>/400/RE/W</u>										
<u>630/KAN/12-12/40/RE/W</u>	1.1	400	3	1400	13500	325	38	83	-20 +60	IP 66
<u>630/KAN/8-8/35/40/RE/W</u>	0.55	400	1.3	1400	10200	205	34	77	-20 +60	IP 66
<u>630/KAN/8-8/40/40/RE/W</u>	0.75	400	2.2	1400	11700	210	33	80	-20 +60	IP 66
<u>KV 100C</u>	0.07	230V, 50Hz	0.32	2460	330	310	2.9	---	-20 +70	IP 44
<u>KV 125C</u>	0.072	230V, 50Hz	0.33	2360	400	300	2.9	---	-20 +70	IP 44
<u>KV 160C</u>	0.1	230V, 50Hz	0.44	2480	750	360	4.3	---	-20 +65	IP 44
<u>KV 200B</u>	0.158	230V, 50Hz	0.69	2500	950	560	5.1	---	-20 +60	IP 44
<u>KV 250C</u>	0.185	230V, 50Hz	0.81	2420	1100	570	5.3	---	-20 +55	IP 44
<u>KV 315B</u>	0.19	230V, 50Hz	0.84	2465	1250	580	6.1	---	-20 +50	IP 44
<u>KV 315C</u>	0.284	230V, 50Hz	1.24	2370	1700	720	6.5	---	-20 +50	IP 44
<u>315/KAN/8-8/35/40/H/T/U</u>	1.1	400	2.8	2800	4050	1850	32	82	-20 +60	IP 66
<u>315/KAN/8-8/50/230/N/T/U</u>	0.3	230	2.6	1350	2730	425	32	73	-20 +60	IP 66

<u>355/ KAN/ 6- 6/40 /400 /H/T U</u>	1.5	400	3.6	2800	6270	1850	37	87	-20 +60	IP 66
<u>355/ KAN/ 8- 8/45 /230 /N/T U</u>	0.3	230	2.6	1350	3540	500	34	74	-20 +60	IP 66
<u>400/ KAN/ 8- 8/35 /400 /H/T U</u>	3	400	6.6	2800	8520	2300	44	89	-20 +60	IP 66
<u>400/ KAN/ 8- 8/45 /230 /N/T U</u>	0.5	230	3.6	1350	5120	520	40	78	-20 +60	IP 66
<u>450/ KAN/ 6- 6/35 /400 /H/T U</u>	3	400	6.6	2800	11200	2150	52	91	-20 +60	IP 66
<u>450/ KAN/ 8- 8/45 /230 /N/T U</u>	0.74	230	5.6	1350	7320	600	45	82	-20 +60	IP 66
<u>500/ KAN/ 8- 8/35 /400 /H/T U</u>	6	400	13.8	2800	15200	2800	69	94	-20 +60	IP 66
<u>500/ KAN/ 8- 8/45 /230 /N/T U</u>	1.1	230	8	1350	9470	670	53	84	-20 +60	IP 66

<u>500/ KAN/ 8- 8/45 /400 /N/T U</u>	1.1	400	2.6	1400	9820	720	49	84	-20 +60	IP 66
<u>560/ KAN/ 10- 10/4 5/40 0/N/ TU</u>	2.2	400	6	1400	13800	930	62	88	-20 +60	IP 66
<u>630/ KAN/ 10- 10/4 5/40 0/N/ TU</u>	3	400	8.6	1400	18100	1100	65	89	-20 +60	IP 66
<u>630/ KAN/ 12- 12/4 5/40 0/L/ TU</u>	1.1	400	4.6	900	12200	520	67	81	-20 +60	IP 66
<u>AFK- 315</u>	0.12	230V	1	1420	2520	---	---	61	---	0
<u>AFK- 355</u>	0.18	230V	1.4	1420	3600	---	---	62	---	0
<u>AFK- 400</u>	0.37	230V	2.8	1420	5400	---	---	65	---	0
<u>AFK- 450</u>	0.55	230V	3.8	1420	7200	---	---	69	---	0
<u>AFK- 500</u>	0.55	230V	2.5	1420	9000	---	---	71	---	0
<u>AFK- 560</u>	0.55	230V	3.8	1420	10800	---	---	72	---	0
<u>315/ KAN/ 10- 10/4 5/40 0/H</u>	0.75	400	1.8	2800	4990	680	20	83	-20 +60	IP 66
<u>315/ KAN/ 8- 8/35 /400 /H</u>	0.55	400	1.4	2800	4050	730	17	78	-20 +60	IP 66

<u>315/ KAN/ 8- 8/50 /230 /N</u>	0.15	230	1.3	1350	2730	170	17	70	-20 +60	IP 66
<u>355/ KAN/ 10- 10/4 0/40 0/H</u>	1.1	400	2.5	2800	6440	880	23	84	-20 +60	IP 66
<u>355/ KAN/ 10- 10/4 5/23 0/N</u>	0.15	230V	1.3	1350	3470	200	20	71	-20 +60	IP 66
<u>355/ KAN/ 8- 8/30 /400 /H</u>	0.75	400	1.8	2800	4520	760	20	78	-20 +60	IP 66
<u>450/ KAN/ 10- 10/4 5/40 0/N</u>	0.55	400	1.3	1400	7750	290	22	80	-20 +60	IP 66
<u>450/ KAN/ 10- 10/5 0/23 0/N</u>	0.55	230	4	1350	8130	275	23	81	-20 +60	IP 66
<u>450/ KAN/ 8- 8/30 /400 /H</u>	1.5	400	3.3	2800	9500	960	27	84	-20 +60	IP 66
<u>450/ KAN/ 8- 8/35 /400 /H</u>	2.2	400	4.8	2800	11700	1050	31	89	-20 +60	IP 66
<u>450/ KAN/ 8- 8/50 /230 /N</u>	0.55	230	4	1350	7910	240	23	80	-20 +60	IP 66
<u>450/</u>	0.55	400	1.3	1400	8200	253	22	81	-20 +60	IP 66

<u>KAN/8-8/50/400/N</u>										
<u>500/KAN/10-10/45/400/N</u>	0.75	400	2.2	1400	10100	320	30	82	-20 +60	IP 66
<u>500/KAN/10-10/50/230/N</u>	0.75	230	5.1	1350	10500	300	29	83	-20 +60	IP 66
<u>500/KAN/8-8/30/400/H</u>	2.2	400	4.8	2800	12300	1080	31	86	-20 +60	IP 66
<u>500/KAN/8-8/35/400/H</u>	3	400	6.9	2800	15100	1130	35	91	-20 +60	IP 66
<u>500/KAN/8-8/40/400/N</u>	0.55	400	1.3	1400	8620	280	30	78	-20 +60	IP 66
<u>500/KAN/8-8/45/230/N</u>	0.55	230	4	1350	9470	265	29	80	-20 +60	IP 66
<u>560/KAN/10-10/45/400/N</u>	1.1	400	3	1400	13800	375	34	85	-20 +60	IP 66
<u>560/KAN/12-12/50/400/N</u>	1.5	400	4.3	1400	15200	445	36	87	-20 +60	IP 66
<u>560/KAN/</u>	0.75	400	2.2	1400	11200	300	33	80	-20 +60	IP 66

<u>8-8/40/400/N</u>										
<u>630/KAN/10-10/45/400/N</u>	1.5	400	4.3	1400	18100	435	39	86	-20 +60	IP 66
<u>630/KAN/12-12/45/400/L</u>	0.55	400	2.3	900	12200	205	35	78	-20 +60	IP 66
<u>630/KAN/12-12/50/400/N</u>	2.2	400	5.8	1400	21000	495	43	90	-20 +60	IP 66
<u>AFS/2-350-055S</u>	0.55	230V	3.4	2860	5750	---	24	78	---	0
<u>AFS/2-400-110S</u>	1.1	230V	7.9	2860	8000	---	26	80	---	0
<u>AFS/4-560-110S</u>	1.1	230V	7	2860	12000	---	37	77	---	0
<u>AFH/2-400-110S</u>	1.1	400V, 50Hz	2.5	2800	6150	---	---	83	---	0
<u>AFH/2-400-110T</u>	1.1	400V, 50Hz	2.5	2800	6150	---	---	83	---	0
<u>AFH/2-450-300T</u>	3	400V, 50Hz	6.5	2800	8400	---	---	85	---	0
<u>AFH/4-400-037T</u>	0.37	400V, 50Hz	1.07	1400	3300	---	---	74	---	0
<u>AFH/4-500-</u>	0.75	400V, 50Hz	1.81	1400	6300	---	---	76	---	0

<u>VB/2-450-300</u>										
<u>AFC-VB/2-500-300</u>	3	400V	6.5	---	---	---	---	---	-20 +40	IP 55
<u>AFC-VB/4-1000-1100</u>	11	400V	21.2	---	---	---	---	---	-20 +40	IP 55
<u>AFC-VB/4-560-150</u>	1.5	400V	4.3	---	---	---	---	---	-20 +40	IP 55
<u>AFC-VB/4-630-220</u>	2.2	400V	4.8	---	---	---	---	---	-20 +40	IP 55
<u>AFC-VB/4-710-400</u>	4	400V	8.1	---	---	---	---	---	-20 +40	IP 55
<u>AFC-VB/4-800-400</u>	4	400V	8.1	---	---	---	---	---	-20 +40	IP 55
<u>AFC-VB/4-900-400</u>	4	400V	8.1	---	---	---	---	---	-20 +40	IP 55
<u>AFC-VB/4-900-750</u>	7.5	400V	14.4	---	---	---	---	---	-20 +40	IP 55
<u>AFC/6-1250-1100</u>	11	400V	22.2	960	75000	---	230	84	---	0
<u>AFC/6-1500-1100</u>	11	400V	22.2	960	80000	---	350	85	---	0
<u>AFC/8-2000-1100</u>	11	400V	25.1	700	120000	---	500	88	---	0

<u>AFC/4-1000-1100</u>	11	400V	21.2	1440	55000	---	160	83	---	0
<u>AFC/4-560-150</u>	1.5	400V	4.3	1440	14000	---	65	82	---	0
<u>AFC/4-630-220</u>	2.2	400V	4.8	1420	18200	---	75	82	---	0
<u>AFC/4-710-400</u>	4	400V	8.1	1440	25500	---	80	83	---	0
<u>AFC/4-800-400</u>	4	400V	8.1	1440	30000	---	85	83	---	0
<u>AFC/4-900-400</u>	4	400V	8.1	1440	32500	---	90	83	---	0
<u>AFC/4-900P-750</u>	7.5	400V	14.4	1440	43500	---	108	83	---	0
<u>AFC/2-250-025S</u>	0.25	230V	1.8	2850	2250	---	15	72	---	0
<u>AFC/2-250-025T</u>	0.25	400V	0.65	2760	2250	---	15	72	---	0
<u>AFC/2-250-037T</u>	0.37	400V	1	2800	2600	---	15	72	---	0
<u>AFC/2-315-037S</u>	0.37	230V	2.5	2860	3400	---	17	74	---	0
<u>AFC/2-315-037T</u>	0.37	400V	1	2800	3400	---	17	74	---	0
<u>AFC/2-315-</u>	0.75	400V	1.9	2800	5000	---	20	77	---	0

<u>075T</u>										
<u>AFC/2-355-055S</u>	0.55	230V	3.4	2860	4500	---	30	77	---	0
<u>AFC/2-355-055T</u>	0.55	400V	1.35	2790	4500	---	30	77	---	0
<u>AFC/2-355-110T</u>	1.1	400V	2.5	2780	5700	---	35	78	---	0
<u>AFC/2-400-150</u>	1.5	400V	3.4	2800	7800	---	37	80	---	0
<u>AFC/2-450-220</u>	2.2	400V	4.7	2800	9500	---	57	81	---	0
<u>AFC/2-450-300</u>	3	400V	6.5	2800	12000	---	57	81	---	0
<u>AFC/2-500-300</u>	3	400V	6.5	2800	15000	---	60	81	---	0