

Radiaalventilaatorid



Tüüp	Võimsus (kW)	Pinge (V)	Vool (A)	Pöörete arv (x/min)	Õhukogus (m ³ /h)	Surve max Pa	Kaal (kg)	Mürategur (dB)	Töötetemperatuur (C)	IP kaitseaste
500/M /6- 6/45	0.37	400V	2.8	1350	8880	225	116	79	-20 +40	IP 66
RS 1000/ 6	18.5	400V, 50Hz	36.6	970	47500	1460	697	80	-20 +60	IP 55
RS 1000/ 6	22	400V, 50Hz	42.4	970	61000	1640	716	82	-20 +60	IP 55
RS 1120/ 6	30	400V, 50Hz	56.3	980	68500	1850	1071	83	-20 +60	IP 55
RS 1120/ 6	37	400V, 50Hz	67.4	980	85000	2110	1212	85	-20 +60	IP 55
RS 1250/ 6	55	400V, 50Hz	99.8	980	95400	2360	1475	86	-20 +60	IP 55
RS	75	400V,	134	985	120600	2630	1596	88	-20 +60	IP 55

1250/6		50Hz								
RS 1400/6	90	400V, 50Hz	161	985	135000	2980	2038	89	-20 +60	IP 55
RS 1400/6	110	400V, 50Hz	196	985	171000	3450	2094	93	-20 +60	IP 55
RS 500/6	0.37	400V, 50Hz	1.24	930	6150	350	115	57	-20 +60	IP 55
RS 500/6	0.55	400V, 50Hz	1.7	930	6850	370	116	59	-20 +60	IP 55
RS 560/6	0.75	400V, 50Hz	2.18	930	8500	430	131	60	-20 +60	IP 55
RS 560/6	1.1	400V, 50Hz	3.03	930	9500	470	133	62	-20 +60	IP 55
RS 630/6	1.5	400V, 50Hz	3.75	950	12000	580	173	66	-20 +60	IP 55
RS 630/6	22.2	400V, 50Hz	5.32	950	15300	610	179	68	-20 +60	IP 55
RS 710/6	3	400V, 50Hz	7.03	950	17000	710	276	69	-20 +60	IP 55
RS 710/6	4	400V, 50Hz	9.3	960	21600	820	286	72	-20 +60	IP 55
RS 800/6	5.5	400V, 50Hz	12.2	960	24200	930	330	73	-20 +60	IP 55
RS 800/6	7.5	400V, 50Hz	16.1	970	30600	1020	368	75	-20 +60	IP 55
RS 900/4	11	400V, 50Hz	22.9	970	34200	1190	500	76	-20 +60	IP 55
RS 900/4	15	400V, 50Hz	30	970	42500	1310	499	78	-20 +60	IP 55
RS 1000/4	55	400V, 50Hz	97.8	1480	76500	3390	832	90	-20 +60	IP 55
RS 1000/4	75	400V, 50Hz	133	1480	95400	3770	941	93	-20 +60	IP 55
RS 310/4	0.18	400V, 50Hz	0.59	1310	2700	290	42	57	-20 +60	IP 55
RS 350/4	0.37	400V, 50Hz	1.06	1360	3850	400	65	60	-20 +60	IP 55
RS 400/4	0.55	400V, 50Hz	1.49	1370	5400	520	75	64	-20 +60	IP 55
RS	0.75	400V,	1.92	1380	6850	610	89	65	-20 +60	IP 55

450/4		50Hz								
RS 450/4	1.1	400V, 50Hz	2.75	1390	7650	660	94	67	-20 +60	IP 55
RS 500/4	1.5	400V, 50Hz	3.52	1400	9500	760	123	69	-20 +60	IP 55
RS 500/4	2.2	400V, 50Hz	4.9	1420	10800	870	129	71	-20 +60	IP 55
RS 560/4	3	400V, 50Hz	6.44	1430	13500	980	141	72	-20 +60	IP 55
RS 560/4	4	400V, 50Hz	8.36	1430	17000	1100	146	74	-20 +60	IP 55
RS 630/4	5.5	400V, 50Hz	11.2	1440	19000	1280	190	75	-20 +60	IP 55
RS 630/4	7.5	400V, 50Hz	14.8	1450	24200	1530	204	78	-20 +60	IP 55
RS 710/4	11	400V, 50Hz	21.1	1450	27000	1720	315	79	-20 +60	IP 55
RS 710/4	15	400V, 50Hz	28.6	1450	34200	1930	326	82	-20 +60	IP 55
RS 800/4	18.5	400V, 50Hz	34.6	1460	38200	2140	402	83	-20 +60	IP 55
RS 800/4	22	400V, 50Hz	41	1470	47500	2260	418	85	-20 +60	IP 55
RS 900/4	37	400V, 50Hz	66.4	1480	54000	2830	630	86	-20 +60	IP 55
RS 900/4	45	400V, 50Hz	80.4	1480	68500	3170	650	88	-20 +60	IP 55
RS 250/2	0.55	400V, 50Hz	1.33	2820	2700	870	33	70	-20 +60	IP 55
RS 280/2	1.1	400V, 50Hz	2.5	2840	3850	1100	43	72	-20 +60	IP 55
RS 310/2	2.2	400V, 50Hz	4.6	2850	5400	1390	52	76	-20 +60	IP 55
RS 350/2	3	400V, 50Hz	6	2900	7650	1850	80	79	-20 +60	IP 55
RS 400/2	4	400V, 50Hz	7.7	2900	9500	2130	95	82	-20 +60	IP 55
RS 400/2	5.5	400V, 50Hz	10.5	2900	12000	2310	108	84	-20 +60	IP 55
RS 450/2	7.5	400V, 50Hz	14.2	2900	13500	2690	124	86	-20 +60	IP 55
RS 450/2	11	400V, 50Hz	20.6	2930	17000	2920	160	88	-20 +60	IP 55

RS 500/2	15	400V, 50Hz	28.7	2940	19000	3350	167	89	-20 +60	IP 55
RS 500/2	18.5	400V, 50Hz	32.5	2940	24200	3700	196	92	-20 +60	IP 55